



BLU2WHITE™ PREMIUM
ELASTOMERIC FINISH COAT
KS0063700 WHITE

PRODUCT DESCRIPTION

Kool Seal® Blu2White™ Elastomeric Roof Coating is a color-changing acrylic finish coat that provides a highly reflective finish to lower interior temperatures and reduce energy costs. This product is formulated with SnowRoof® technology for easy coverage – Blu2White™ coating is blue in color during application, and will transition to bright white when drying, usually within 24 hours. Transition time will depend on environmental conditions and amount of sunlight. Kool Seal® Blu2White™ coating provides excellent waterproofing capabilities.

FEATURES AND BENEFITS

- Easy Coverage SnowRoof® Technology – Goes on Blue, Dries White
- Limited Lifetime Warranty
- Dramatically lowers roof and interior temperatures, reducing energy costs
- Dirt Pickup Resistant

RECOMMENDED USES

- Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, existing asphaltic and elastomeric roof coatings and other approved surfaces.
- NOT for use on roof shingles
- It is recommended to prime EPDM rubber roofs with Kool Seal Elastomeric Base Coat Gray

ORDERING INFORMATION

Part Number	Color/Size
KS0063700-16	White (0.9 Gallon)
KS0063700-20	White (4.75 Gallon Pail)

PRODUCT CHARACTERISTICS

Technology	100% Acrylic
Color	Blue*
Volume Solids	42% ± 2%
Weight Solids	56% ± 2%
VOC	16 g/L
Drying Time**	Exposure to rain or heavy dew: 4-12 hours Between coats and before roof traffic: 24 hours minimum

*Will transition to white upon exposure to direct sunlight.

**Dry time is temperature, humidity and film thickness dependent.

COVERAGE RATES

It is recommended to prime the roof substrate with Kool Seal Elastomeric Base Coat Gray at 50-100 sq. ft. per gallon followed by Kool Seal Blu2White Premium Elastomeric Finish Coat. at 50-100 sq. ft. per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended.

EPDM rubber roofs must be primed with Kool Seal Elastomeric Base Coat Gray (refer to KS0034600 for coverage rate).

DO NOT DILUTE THIS PRODUCT.

SURFACE PREPARATION

Surface must be power washed (minimum 2,000 psi) to remove dirt and other foreign matter, which could prevent proper adhesion. Surfaces must be completely dry prior to coating. **IMPORTANT:** Where ponding water conditions persist beyond 48 hours, roof drains or other corrective measures must be installed to eliminate water build up prior to coating the roof. Repair all cracks, breaks, open seams and other imperfections with Kool Seal® Storm Patch® Acrylic Patching Cement and Kool Seal Storm Patch Polyester Fabric. Apply Kool Seal Storm Patch Acrylic Rust Primer to existing rusted areas.

APPLICATION

Do not apply below 50 °F (10 °C) or when rain is forecast. Applications during periods of low temperature and high humidity will extend dry time. **KEEP FROM FREEZING.**

Thoroughly mix product prior to application. Airless spray or apply with a low-nap roller or broom at the appropriate coverage rate. Allow adequate drying time between coats. Two coats recommended. For specific application guidelines, call 888-321-KOOL (5665).

CLEANUP

Warm, soapy water

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED LIFETIME WARRANTY

From the date of purchase, Kool Seal and The Sherwin-Williams Company (together the "Company") warrant to the original Purchaser that the Kool Seal Blu2White™ Elastomeric Roof Coating (the "Product") will be free from defects in materials and manufacturing. Under this warranty, the Company agrees to furnish, at no charge during the warranty period, a quantity of material sufficient to replace the portion of the Product proven to be defective when applied according to the Product's written instructions and in applications recommended by the Company as suitable for the Product. In order to maintain the Warranty, the Purchaser must re-apply one coat of the Product every 5 years. This warranty is made to the original Purchaser and is not transferrable.

THIS WARRANTY IS THE PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE COMPANY REGARDING THE PRODUCT. THE PURCHASER AGREES THAT IN NO EVENT SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, INDIRECT, PUNITIVE OR OTHER DAMAGES INCLUDING, BUT NOT LIMITED TO, DAMAGES TO ANY PROPERTY OR LOST PROFITS, ARISING FROM OR RELATED TO THIS WARRANTY OR THE SPECIFICATIONS, INSTALLATION OR PERFORMANCE OF THE PRODUCT BASED UPON BREACH OF WARRANTY, NEGLIGENCE OR ANY OTHER THEORY OF LIABILITY.

THE COMPANY MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, EXCEPT AS STATED ABOVE AND HEREBY DISCLAIMS ANY AND ALL OTHER WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE REGARDING THE PRODUCT.

TECHNICAL SERVICES

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.